## WORK IN PARKING STRIP WITH MINOR ENCROACHMENT, SIDE STREET -RIGHT SIDE OF INTERSECTION WORK WORK **GAOR** DRAWING NOT TO SCALE INDICATE NORTH FT FT WORK ZONE FT SHALL MAINTAIN 2-10' MINIMUM LANE WIDTHS AT ALL TIMES FOR 2 WAY TRAFFIC OR 20' MINIMUM WIDTH FOR 2 WAY TRAFFIC ON STREETS WITHOUT LANE **STRIPING** FT STREET NAME ROAD WORK AHEAD **BETWEEN** AND SHALL MAINTAIN 10' MINIMUM LANE WIDTH AT ALL TIMES POSTED SPEED ALL LENGTHS ARE MINIMUM **DISTANCES UNLESS** OTHERWISE NOTED FOR DIMENSIONS CONSULT CITY OF SALEM "TEMPORARY TRAFFIC CONTROL SPACING TABLES" PLACE SIGNS ON ALL SIDE STREETS, WITHIN THE TRAFFIC CONTROL ZONE

Sight distance shall be maintained at all public and private intersections and driveways. If sight distance is not achievable, prior approval by the City Traffic Engineer is required to either restrict turn movements or use flaggers and shall include coordination with the affected property/business owner(s).